

**SPECIFICATION SHEET # 6020, ANTIQUE WALNUT T&G FLOORING
February 15th, 2007**

1. Species

Walnut

2. Source

Barns, corncribs, stables, mills, homes and other buildings
and agricultural structures from different locations in North America

3. Moisture Content/Stability

Kiln-Dried: Reclaimed Walnut T&G Flooring is cut from stock which is generally very dry and seasoned and is then kiln-dried. The resulting lumber is much more stable and less prone to shrinkage than is green lumber.

4. Knots

Unlimited. Some knots are loose, broken or fallen out.

5. Nail Holes

Nails and other fasteners are removed, leaving occasional nail holes. Staining around nail and fastener holes is common.

6. Checking/Cracks

Surface checking is allowed; some cracking is allowed as long as board is sound.

7. Grain Pattern

Mixed

8. Standard Dimensions

a) Thickness (net): 3/4"; b) Width: Random 3-5", wider boards (6 to 8" and 9"+) may be available as a special order; and c) Length: 1' to 12'.

9. Surfacing

Smooth, Circlesawn or Wirebrushed

10. Color/Appearance

Some boards are more rustic than others; in general, boards have a nice aged appearance, with checking, knots, nail holes, stain, worm holes, some water-stain, etc. (all in varying degrees).

11. Weight

Typically, approximately 3 pounds per board foot