

**SPECIFICATION SHEET # 6022, ANTIQUE CHESTNUT T&G FLOORING  
February 2nd, 2007**

**1. Species**

Chestnut

**2. Source**

Barns, corncribs, stables, mills, homes and other buildings  
and agricultural structures from different locations in North America

**3. Moisture Content/Stability**

Kiln-Dried: Reclaimed Chestnut T&G Flooring is cut from stock which is generally very dry and seasoned and is then kiln-dried. The resulting lumber is much more stable and less prone to shrinkage than is green lumber.

**4. Knots**

Unlimited. Some knots are loose, broken or fallen out.

**5. Nail Holes**

Nails and other fasteners are removed, leaving occasional nail holes. Staining around nail and fastener holes is common.

**6. Worm Holes**

Reclaimed Chestnut T&G Flooring may have worm holes. The extent of worm holes will vary from none to extensive depending on the piece.

**7. Checking/Cracks**

Surface checking is allowed; some cracking is allowed as long as board is sound.

**8. Grain Pattern**

Mixed

**9. Standard Dimensions**

a) Thickness (net): 3/4"; b) Width: Random 3-5", wider boards (6 to 8" and 9"+) may be available as a special order; and c) Length: 1' to 12'.

**10. Surfacing**

Smooth, As-Is or Skip-Planed

**11. Color/Appearance**

Some boards are more rustic than others; in general, boards have a nice aged appearance, with checking, knots, nail holes, stain, worm holes, some water-stain, etc. (all in varying degrees).

**12. Weight**

Typically, approximately 3 pounds per board foot