

**SPECIFICATION SHEET # 6042, TRAILBLAZER MIXED HARDWOOD T&G FLOORING
January 12th, 2008**

1. Introduction

When the first settlers moved into new regions of our expanding nation, they cleared small plots of ground for subsistence farming and used the felled trees for logs and timbers to construct homes for themselves and barns for their livestock. Because these resourceful settlers had to use what was available to them, they often did not discriminate among wood species--if the trees they felled were solid and durable they were used in the needed structures. It is in that same spirit of resourcefulness, economy and good stewardship that Trestlewood offers Trailblazer Mixed Hardwood T&G Flooring. Rest assured that the flooring you purchase will be the same mix of hearty North American species as was used by our great, great grandfathers more than a century ago.

2. Species

Mixed Hardwood. May include Oak, Elm, Hickory, Ash, Maple, Beech, others

3. Source

Barns, corn cribs, stables, mills, homes and other buildings and agricultural structures from different locations in North America

4. Knots

Unlimited. Some knots are loose, broken or fallen out.

5. Nail/Bolt/Worm holes

Random nail holes; occasional bolt holes or peg holes; regular worm holes. Nail and bolt holes commonly have some stain surrounding the hole.

6. Checks/Cracks

Moderate surface checking; some cracking is allowed as long as the board is sound.

7. Grain pattern

Mixed

8. Standard Dimensions

a) Thickness: 3/4"; b) Width: 3" to 7"; c) Length: 2 to 10' with no more than 5% of footage to be less than 4'.

9. Textures Available

Smooth and Circle-Sawn

10. Other

Characteristics apply to the flooring board's finished face.