

Species

Southern Yellow Pine

Source

Texas walkway planks

Holes

Occasional random nail holes; no bolt holes; some staining around the nail holes or on the face is allowable

Knots

Weathered Pine Jackets are not sorted for knot content.

Checking/Cracks

Moderate amounts of surface checking allowed

Grain Pattern

Vertical, flat or mixed

Moisture Content/Stability

Air-Dried

Standard Dimensions

a) Thickness (net): 3/8" +/- 1/8"; b) Width (net): 9 - 9.5"; and c) Length: random, in 1' increments up to 7'

Weight

Typically, approximately 1 pound per square foot

Surfacing

Weathered on one face and Band-Sawn on one face

Appearance Variation

Boards can vary in appearance from piece to piece and even within a piece. The characteristics described on this specification sheet generally apply to each board's featured face. The opposite face and edges can differ from the featured face in texture, coloring, and other characteristics unless otherwise noted. Weathered lumber / barnwood will have at least one weathered face. The opposite face and edges can be any combination of weathered and fresh-sawn. If weathered, the weathering will often be different (amount, mix of colors, etc) than on the featured face.

Trestlewood sometimes uses one or more "juicing" processes to help fresh-sawn and/or less weathered/aged faces/edges blend in with weathered faces/edges. All else being equal, juicing is more likely to be used in situations where (a) lumber is cut from timbers or wider lumber (thereby creating fresh-cut faces and/or edges); (b) Buyer wants all (or most) faces/edges to be weathered/aged; and/or (c) Buyer desires to increase the consistency of the weathered/aged look from face to face.

