

Species

Various depending on source; likely softwoods

Source

Various reclaimed wood projects

Standard Dimensions

Vary depending on source: a) Common Thickness: 1.5" to 4" (nominal); b) Common Width: 5" (nominal); c) Common Lengths: from 4' to 14'+.

Moisture Content/Stability

Air-Dried

Knots

Unlimited knots; some tight, some fallen out

Metal

Nails, bolts and other fasteners can be removed, cut flush or left as-is. Some metal can be broken off inside the beam.

Checking/Cracks

Unlimited, but generally sound. Some falldown is to be expected.

Grain Pattern

Mixed

Surfacing

Weathered (degree of weathering varies); original surface may have been rough-sawn, band-sawn or planed, but may have been worn rather smooth; potential for some surface degradation (water damage, surface rot, "punkiness").

Profile

Original/As-Is Tongue and Groove (T&G). Given the reclaimed nature of the decking, tongues and grooves may be damaged or broken and will generally not fit together as well as lumber with fresh-milled T&G. Some sources may have beaded faces or other original milled characteristics, which may also be somewhat damaged or broken. Some falldown is to be expected and, depending on application, should be taken into account when determining order quantity.

Weight

Depends on species mix. Typically, 2.5 - 3.0 pounds per board foot.

Appearance Variation

Boards can vary in appearance from piece to piece and even within a piece. Opposite faces and edges especially can differ in texture, coloring, paint, and other characteristics.

Lead-Based Paint

Weathered Decking with Original T&G may have originally been painted with lead-based paint. Trestlewood does not test for lead content and sells this product as-is. Buyer understands that it must determine which uses are appropriate for this product.

